### Roctec Disk Drives Drive You to Success



RF302BS 3.5" 1MB external FDD for IBM PC RF322BS 3.5" 2MB external FDD for IBM AT RF542BS 5.25" 360KB external FDD for IBM PC RF552BS 5.25" 1.2MB external FDD for IBM AT



## 3.5" Floppy Disk Drive: Internal/External Switchable RF302BS, RF322BS

#### SPECIFICATIONS

Model	RF302BS	RF322BS
CAPACITY	1MB Unformatted	2MB Unformatted
HEAD DENSITY	Double	High
NO. OF HEADS	2	2
TRACK DENSITY	135TPI	135TPI
SPIN SPEED	300RPM	300RPM
STEP RATE	3ms	3ms
TRANSFER RATE	250KBPS	500KBPS
POWER	+5V	+5V
POWER SOURCE	Computer	Computer
INTERFACE	DIL 37with Accessory Card	DIL 37 with Accessory Card
CASE	Metal (Ivory)	Metal (Ivory)
PANEL	lvory	lvory
DIMENSIONS(MM)	208 x 104 x 32.5	208 x 104 x 32.5
SYSTEM	IBM-PC with FDD controller	IBM-PC-AT with FDD controller
DISPLAY	Red LED for active	Red LED for active

# 5.25" Floppy Disk Drive: Internal/External Switchable RF542BS, RF552BS

#### SPECIFICATIONS

Model	RF542BS	RF552BS
CAPACITY	500KB Unformatted	1.6MB Unformatted
HEAD DENSITY	Double	High
NO. OF HEADS	2	2
TRACK DENSITY	48TPI	96TPI
SPIN SPEED	300RPM	360RPM
STEP RATE	6ms	3ms
TRANSFER RATE	250KBPS	500KBPS
POWER	+5V, +12V	+5V, +12V
POWER SOURCE	Computer	Computer
INTERFACE	DB37 with Accessory Card	DB37 with Accessory Card
CASE	Metal (Ivory)	Metal (Ivory)
PANEL	Black or Ivory	Black or Ivory
DIMENSIONS(MM)	285 x 150 x 50	285 x 150 x 50
SYSTEM	IBM-PC with FDD controller	IBM-PC-AT with FDD controller
DISPLAY	Red LED for active	Red LED for active

IBM PC/XT, PS/2 ARE REGISTERED TRADEMARKS OF INTERNATIONAL BUSINESS MACHINES CORP. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

